## BMP Maintenance and Inspection Checklist Dry Extended Detention Basin

[Note: a separate form must be used for each BMP]

Project Name:					
Project Address:					
Owner's Name:					
Owner's Address: Recorded Book / Page Number of the Lot:					
BMP Location:					
Date:					
Inspector:					
Inspector Address/Phone Number:					
Date Last Inspected:					

Maintenance Item	Satisfactory	Unsatisfactory	Comments/Actions Required			
1. Debris Cleanout						
Clear of trash and debris						
2. Vegetation Management						
Banks / surrounding areas mowed						
Unwanted vegetation present						
3. Erosion						
Evidence of soil erosion on banks,						
contributing drainage areas or bottom of pond						
4. Sedimentation						
Forebay (if present) sediment inspection						
(cleanout every 7 years or when 50% full)						
Sediment level in pond						
5. Energy dissipaters						
Condition of dissipater at inlets						
Condition of dissipater at outfall						
6. Outlet / Inlet						
Condition of orifice (drawdown device) /						
trash rack						
Condition of outlet						
Condition of inlet						
7. Mechanical devices						
Inspection of all valves, etc. (exercise yearly)						
8. Dewatering						
Evidence of standing water						
9 Structural Integrity	·					

Evidence of structural damage (leaks, cracks,				
etc)				
10. Emergency Spillway & Dam				
Condition of spillway				
Condition of dam				
11. Miscellaneous				
If applicable: Attach to this form document may be provided in the form of a bank state and withdraws for the previous 12 months.  Maintenance Actions Taken: [If any of the actions taken and time table for correction	temen · e abov	nt wh	nich includes the current balance ems were marked "U" for unsati	e, as well as deposits
See notes listed	. Atta		uditional pages as necessary.	
Additional Comments:				
The measuring device used to determine the streading and not readily penetrate into accumu			<del>_</del>	rive an accurate depth
When the sediment removal elevation is		feet	in the main pond, the sediment sh	ould be removed.
When the sediment removal elevation is		feet	in the forebay, the sediment shoul	d be removed.
			SIN DIAGRAM L IN THE BLANKS)	
	🕀 ві	ENCHI	MARK ELEVATION	
	RARY P DLUME 25% SEDIME STORAG	ENT	SEDIMENT REMOVAL ELEVATION	TEMPORARY POOL VOLUME  25% SEDIMENT STORAGE

**FOREBAY** 

**MAIN POND** 

Based upon my inspection of the constructed BMP described herein on						
Inspector's Signature	Date					

[Note: The Stormwater Control Ordinance requires that inspections be conducted of all BMPs beginning within one (1) year from the date of record drawing certification and each year thereafter and that these inspections be completed by a qualified professional as defined in Section 23-33 of the Ordinance. All inspections must be documented and submitted using this form. The inspection form must be signed by the inspector and mailed to the City Engineer at the following address: City of Fayetteville, City Engineer, 433 Hay Street, Fayetteville NC 28301]